

DME or GNSS ARRIVAL PROCEDURES MACKAY, QLD (YBMK) Page 1

1 DEC 2022

ATIS 112.7 128.0	SMC 121.7	TWR 124.5	CORAL APP (MK) 125.65	CTAF+AFRU (AH) 124.5	AFRU+PAL (AH) 124.5	FIA (AH) BN CEN 135.5	Bearings are Magnetic Elevations in FEET AMSL
---------------------	--------------	--------------	--------------------------	-------------------------	------------------------	--------------------------	--

25 NM MSA
R-320°
B-140°
MK VOR or NDB
4700
R-150°
B-326°
2500

**DME USING MK DME
REFERENCE WAYPOINT MK VOR**

10 NM MSA 3100

AD ELEV 19

SECTOR A

VOR or NDB

MISSED APPROACH:
TURN LEFT,
TRACK 130°.
CLIMB TO 2500FT.

NM TO MK VOR	22	15	11	8	5	4	2	0						
CIRCLING MINIMA	A,B: 710-2.4			C: 900-4.0			D: 1160-5.0							
NM TO MK VOR	11	10	9	8	7	6	5	4	3	2	1.4	1	0.7	0.2
ALT (3.29° APCH PATH)	4500	4150	3800	3450	3100	2750	2400	2060	1710	1360	1160	1010	900	710

SECTOR B

VOR or NDB

MISSED APPROACH:
TURN AS APPROPRIATE,
TRACK 130°.
CLIMB TO 2500FT.

NM TO MK VOR	25	17	15	13	8	6	3	0							
CIRCLING MINIMA	A,B: 810-2.4			C: 900-4.0			D: 1160-5.0								
NM TO MK VOR	13	12	11	10	9	8	7	6	5	4	3	2	1.9	1.1	0.9
ALT (3° APCH PATH)	4700	4370	4050	3730	3410	3090	2770	2460	2140	1820	1500	1180	1160	900	810

SECTOR C

VOR or NDB

MISSED APPROACH:
TURN RIGHT,
TRACK 060°.
CLIMB TO 2500FT OR
AS DIRECTED BY ATC.

NM TO MK VOR	25	17	15	13	8	5	3	0							
CIRCLING MINIMA	A,B: 710-2.4			C: 900-4.0			D: 1160-5.0								
NM TO MK VOR	14	12	10	9	8	7	6	5	4	3	2	1.9	1.1	1	0.5
ALT (3° APCH PATH)	5000	4370	3730	3410	3100	2780	2460	2140	1820	1500	1180	1160	900	870	710

Changes: CORAL APP FREQUENCY.

BMKDG01-173