

1 DEC 2022

ATIS 114.1 133.5 276	ACD 128.1	SMC 121.8 264.6	TWR 118.3	FIA (AH) BN CEN 120.55	CTAF+AFRU (AH) AFRU+PAL (AH) 118.3	AWIS (AH) 133.5	Bearings are Magnetic Elevations in FEET AMSL
-------------------------	--------------	--------------------	--------------	------------------------------	--	--------------------	--

**DME USING TL DME REFERENCE WAYPOINT TL VOR**

**SPEED**  
MAX IAS 250KT  
BELOW 10,000FT

10 NM MSA 3600

AD ELEV 18

\* NO CIRCLING IN SECTOR EAST OF RWY 01 & RWY 19.

**SECTOR A**

VOR or NDB

**MISSED APPROACH:**

TURN RIGHT,  
TRACK 290°.  
CLIMB TO 4700FT OR  
AS DIRECTED BY ATC.  
MAX IAS 200KT.

NM TO TL VOR	25	15	13	7	5	0								
<b>CIRCLING MINIMA</b>	A,B: 1350-2.4			C: 1350-4.0		D: 1350-5.0								
NM TO TL VOR	13	12	11	10	9	8	7	6	5	4	3	2.5		
ALT (3° APCH PATH)	4700	4380	4060	3740	3420	3110	2790	2470	2150	1830	1510	1350		

**SECTOR B**

VOR or NDB

**MISSED APPROACH:**

TURN LEFT OR RIGHT,  
AS REQUIRED  
TRACK 290°.  
CLIMB TO 4700FT OR  
AS DIRECTED BY ATC.

NM TO TL VOR	25	15	14	10	5	0								
<b>CIRCLING MINIMA</b>	A,B: 1410-2.4			C: 1410-4.0		D: 1410-5.0								
NM TO TL VOR	12.8	12	11	10	9	8	7	6	5	4	3	2	0.9	
ALT (3° APCH PATH)	5200	4930	4610	4290	3970	3650	3330	3020	2700	2380	2060	1750	1410	

**SECTOR C**

VOR or NDB

**MISSED APPROACH:**

TURN LEFT,  
TRACK 290°.  
CLIMB TO 4700FT OR  
AS DIRECTED BY ATC.

NM TO TL VOR	25	16	13	6	0									
<b>CIRCLING MINIMA</b>	A,B: 2850-2.4			C: 2850-4.0		D: 2850-5.0								
NM TO TL VOR	10.4	10	9	8	7	6	5	4	3					
ALT (3° APCH PATH)	5200	5080	4770	4450	4130	3810	3490	3180	2850					

Changes: SEC B DIST/ALT TABLE.

BTLDG01-173