


GNSS ARRIVAL PROCEDURES GLADSTONE, QLD (YGLA)

25 MAR 2021

AWIS 126.85	FIA BN CEN 119.55	CTAF+AFRU 118.8	AFRU+PAL 118.8	Bearings are Magnetic Elevations in FEET AMSL
-----------------------	-----------------------------	---------------------------	--------------------------	--




25 NM MSA

REFERENCE WAYPOINT GLA VOR

GLA VOR 116.3

VOR: POSSIBLE EXCESSIVE NEEDLE FLUCTUATIONS BELOW 10,000FT BETWEEN R-275° AND R-300°





10 NM MSA 5000

*
NO CIRCLING
SOUTH RWY 10/28

AD ELEV 59

SECTOR C






MISSED APPROACH:


TURN AS APPROPRIATE, TRACK 065°. CLIMB TO 5000FT.

MAP TURN MAX IAS 210KT.

NM TO GLA VOR	25	15	13	8	6	2	0	0	0	0	0	0	0	0
CIRCLING MINIMA	A,B: 1230-2.4			C: 1230-4.0			D: N/A							
NM TO GLA VOR	9.6	9	8	7	6	5	4	3	2	1	0.9			
ALT (3° APCH PATH)	4000	3800	3480	3160	2850	2530	2210	1890	1570	1250	1230			

SECTOR D





MISSED APPROACH:

TURN LEFT, TRACK 065°. CLIMB TO 5000FT.

NM TO GLA VOR	25	18	15	10	6	5	3	0	0	0	0	0	0	0
CIRCLING MINIMA	A,B: 1230-2.4			C: 1230-4.0			D: N/A							
NM TO GLA VOR	12.5	12	11	10	9	8	7	6	5	4	3	2	1	0.6
ALT (3° APCH PATH)	5000	4850	4530	4210	3900	3580	3260	2940	2620	2300	1990	1670	1350	1230

Changes: MINIMA, SECTOR C STEP ALT, SECTOR D 10NM FIX.

GLADG01-166