

ILS-Z or LOC-Z RWY 18
AVALON, VIC (YMAV)

ATIS 118.2 116.1 AWIS (AH) 116.1 AV APP 133.55 TWR 120.1 FIA (AH) ML CEN 135.7 CTAF+AFRU (AH) 120.1 AFRU+PAL (AH) 120.1

37 50 00S 144 20 00E 144 30 00E 144 40 00E

38 00 00S 38 10 00S

11°E

TEMPL (9.3 IAV)

1142 IKANO (4.1 IAV)

0.8 IAV

176°

176°

421

25 NM MSA

3700 2900 2500

R-020° R-065° R-280°

AV VOR

10 NM MSA 2500

144 20 00E 144 30 00E 144 40 00E

Scale 1:500,000 5NM

Holding at TEMPL

066° 246° 356°

TR IN	TURN	TIME	MIN ALT	DME LMT
176°	Left	1	3000	15

* NO CIRCLING *

AD ELEV 35

Bearings are Magnetic Elevations in FEET AMSL

TRACK 176°.
CLIMB TO 3000ft.



CATEGORY	A	B	C	D/D _L
S-I ILS		390 (358)	2.0 (VIS 1.5 WITH ACTUAL QNH)	
S-I LOC		620 (585-3.3)		
CIRCLING *	660 (625-2.4)		760 (725-4.0)	830 (795-5.0)
ALTERNATE	(1125-4.4)		(1225-6.0)	(1295-7.0)

2. HLDG PATTERN
NOT CONTAINED
WITHIN CTA.

MAVII02-182