## 21 MAR 2024

ZI MAR 2024 MILLBOOKHE, VIC (I MINIL)					
ATIS 114.1 118.0	APP <b>132.0</b>	TWR <b>120.5</b>	SMC <b>121.7</b>		Bearings are Magnetic Elevations in FEET AMSL
NOT TO SCALE	:				SPEED MAX IAS 250KT BELOW 10,000FT
	MIN IA				RNP 1
# 1	YMEN  **256**  (3) SHEED	2500 256° - 250 256° - 256°		NM E	TC APCH SPEEDS  I FM TD SPEED KT  GEKA 185 -160  SHEED 160 -150
	<u>2500</u>	LOCIVA	MIC	IAS AT 230KT	25 NM <i>MSA</i>
			5000 V		4500 B-080° (YMM) B-260° ARP
# CAUTION: R Threshold Ide Essendon Air	RWY 34 is indicated entification Lights, rport 5NM SE of M	l by Runway L.	<u>10.</u>	000 ♦ WAREN	3700 10 NM MSA 3300

## **ARRIVAL: WAREN EIGHT VICTOR**

## **RWY 34**:

Changes: VAR, Editorial.

- Cross WAREN AT or ABV 10,000ft
- From WAREN track 319° to MICHM Cross MICHM AT or ABV 5000ft IAS AT 230KT from MICHM
- Track 321° to MONTY
  - Cross MONTY BTN 4000ft and 6000ft
- Turn LEFT, track 256° to EGEKA MAX IAS 185KT from EGEKA
- Track 256° to SHEED
- Cross SHEED AT or ABV 2500ft MIN IAS 150KT from SHEED

  Track 256° VISUAL to ASUKI
  Turn RIGHT for VISUAL intercept of
- final RWY 34

## COMMUNICATIONS FAILURE: PROCEDURE IN IMC

australia

- Squawk 7600, comply with vertical navigation requirements, but not below MSA.
- Track via the latest STAR clearance to the nominated runway, then fly the most suitable approach in accordance with ERSA EMERG Section 1.5.

© Airservices Australia airservices