

VOR RWY 09
MELBOURNE, VIC (YMML)

ATIS
114.1 118.0

APP
132.0

TWR
120.5

SMC
121.7

NAVAID RQ:
• DME

Holding as advised by ATC

TR	TURN	TIME	MIN ALT	DME LMT

MAX IAS 185KT

ATC APCH SPEEDS

NM FM THR	SPEED KT
NAOMI	185 - 160
5	160 - 150

AD ELEV 434

Bearings are Magnetic
Elevations in FEET AMSL

DIST TO ML DME	9	8	7	6	5	4	3	2.5						
ALT (3° APCH PATH)	3000	2690	2370	2050	1740	1420	1100	950						

GNSS permitted in lieu of DME
Reference waypoint ML VOR

MISSED APPROACH:
TRACK 080°
CLIMB TO 4000ft OR
AS DIRECTED BY ATC.

4000 3°
‡ WILDE
3000
‡ MISCH
3000
2100
‡ NAO ML
LR-248°
LR-271°
2690
2050
1800
1400
080°
1420
MDA
MAP
080°
THR 09 ELEV 395

NM TO ML DME: 10, 10, 8, 6, 4, 1.5, 0

CATEGORY	A	B	C	D
S-I VOR/DME	950 (555-3.2)			
CIRCLING	1140 (706-2.4)	1450 (1016-4.0)	1600 (1166-5.0)	
ALTERNATE **	(1206-4.4)	(1516-6.0)	(1666-7.0)	

1. MAX IAS:
NAOMI : 185KT.
- * 2. SPECIAL ALT MNM
NOT APPLICABLE.
- ‡ 3. ACFT MAY BE
RADAR VECTORED
TO IAF.

MMLVO01-178