

VOR RWY 12
ADELAIDE, SA (YPAD)

ATIS 116.4 134.5
APP 118.2 124.2
TWR 120.5
SMC 121.7

NAVAID RQ:
• DME

Holding at AD R-304° / 10 DME

TR IN TURN	TIME	MIN ALT	DME LMT
124° Left	1	3000	

ATC APCH SPEEDS

NM FM THR	SPEED KT
10	185-160
5	160-150

VOR/DME 116.4

AD ELEV 20
Bearings are Magnetic
Elevations in FEET AMSL

Scale 1:500,000

0 5NM

10 NM MSA 3800

25 NM MSA

R-360°
R-220°
R-149°

1900
3800
2700

AD VOR

4 DME AD
3NM THR 05/23/30
NO CIRCLING

Adelaide Parafeld

538
493
591
422
1365
2779
901

LR-318°AD
LR-290°AD
R-330°AD
R-270°AD
R-140°

10 AD
10 AD
10 AD
5 AD

34 50 00S
35 00 00S
138 20 00E
138 30 00E
138 40 00E
34 50 00S

8° E

DIST TO AD DME	9.6	9	8	7	6	5	4	3	2	1.6	1.5		
ALT (3° APCH PATH)	3000	2830	2510	2190	1870	1550	1230	910	600	470	450		

MISSED APPROACH:
TURN RIGHT, TRACK ON
R-140°. CLIMB TO 3800FT
OR AS DIRECTED BY ATC.

GNSS permitted in lieu of DME
Reference waypoint AD VOR

AD VOR/DME

THR 12 ELEV 14

MAPt

MDA

1500

3000

3800

10

5

0

3°

124°

R-270° AD

R-330° AD

R-304° AD

LR-290° AD

LR-318° AD

R-140°

NM TO AD DME

NOTES

- * 1. NO CIRCLING S OF RWY 05/23 BEYOND 4 DME AD OR BEYOND 3NM FM THR 05/23/30.
- ** 2. SPECIAL ALTN MNM 850/4.0KM.
- ‡ 3. ACFT MAY BE RADAR VECTORED TO FNA.
- 4. **COLOUR:** SEE SPEC NOTICES.

CATEGORY	A	B	C	D
S-I VOR/DME	450 (430-2.4)			470 (450-2.5)
CIRCLING *	900 (880-2.4)		1000 (980-4.0)	1000 (980-5.0)
ALTERNATE *	(1380-4.4)		(1480-6.0)	(1480-7.0)

PADVO03-170