

5 SEP 2024

NOT TO SCALE

SPEED
MAX IAS 250KT
BELOW 10,000ft


RNP1

IAS
AT 230KT

MAX IAS
185KT

KAGMI 3000 FL110 3000 9000 3000
103° (12) 103° (7) 107° (12)
BITAP KALBO TEMA

ATC APCH SPEEDS	
NM FM TD	SPEED KT
RWY 03 BITUM	185 -160
RWY 21 HAIGH	185 -160



10 NM MSA 2700

PERTH
PH:.... VOR/DME 113.7

MAX IAS
185KT

IAS
AT 230KT

- From KAGMI, track 103° to BITAP
Cross BITAP AT or BLW FL110
- Track 103° to KALBO
Cross KALBO AT 9000ft
- Turn RIGHT, track 107° to TEMAP
Cross TEMAP AT or BLW 6000ft
- Track 107° to IPMOR
- Then follow ARRIVAL Instructions.

RWY 03:

- Turn RIGHT, track 153° to HAYCO
- Turn LEFT, track 102° to SADOL
IAS AT 230KT from SADOL
- Track 102° to HARMN
- Turn LEFT, track 015° to BITUM
for ILS, RNP Z or LOC
RWY 03 APPROACH
MAX IAS 185KT from BITUM

- Turn LEFT, track 089° to GORMA
- Track 089° to WOOFY
for ILS, RNP, LOC or
VOR RWY 21 APPROACH
IAS AT 230KT from WOOFY
MAX IAS 185KT from HAIGH

- Squawk 7600, comply with vertical navigation requirements, but not below MSA.
- Track via the latest STAR clearance to the nominated runway, then fly the most suitable approach in accordance with ERSA EMERG Section 1.5.

PPHSR18-180