


BELLEVUE**ELEV 1555****AVFAX CODE 6105**

WA
273646S 1203538E UTC +8
VAR 1 DEG E

YBLU
CERT

AD OPR IGO Limited, PO Box 496, South Perth, WA, 6951. Email:
craig.gaffney@igo.com.au. PH AD Manager 0407 505 397.

REMARKS

Restricted OPS - PPR from AD OPR.

HANDLING SERVICES AND FACILITIES

Terminal facilities. No fuel available. Contact ARO.

APRONS AND TAXIWAYS

TWY A - Code C, 15M sealed.

AERODROME OBSTACLES

1. Terrain 1,832FT AMSL BRG 332 DEG MAG APRX 2.8NM FM ARP, penetrates OBST limitation SFC by 82FT.
2. Tower 1,795FT AMSL BRG 297 DEG MAG APRX 1.6NM FM ARP.
3. Cranes:
 - a. 1,767FT AMSL BTN BRG 330-340 DEG MAG APRX 1.3NM FM ARP (temporary). Infringes HZS up to 50FT.
 - b. 1,763FT AMSL BRG 315 DEG MAG 1.24NM FM ARP. Head frame infringes inner HZS by up to 110FT.

PHYSICAL CHARACTERISTICS

01/19 006 66a PCN 32 / F / C / 1000 (145PSI) / T Sealed. WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 01/19	LIRL(3)		SDBY PWR AVBL BY PRIOR ARRANGEMENT
RWY 01/19	PAPI(1)	3.0 DEG 49FT	SDBY PWR AVBL BY PRIOR ARRANGEMENT
RWY 01/19	PTBL(2)		BY PRIOR ARRANGEMENT

- (1) Left side only. Manual activation with 30MIN PN.
- (2) EMERG only. 60MIN PN. CTC ARO.
- (3) 30MIN PN.

OTHER LIGHTING

1. SDBY PWR switchover time: 15 MIN.
2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 118.95 Circuit area

LOCAL TRAFFIC REGULATIONS

1. All ACFT to use turn pads, MAX turn radius at MNM speed.
2. All ACFT ABV 5,700KG MTOW must park on marked bays using appropriate lead-in lines.

FLIGHT PROCEDURES

Right hand circuit on RWY 01 due to terrain to the NW of the AD.

CTAF 126.5

AFRU at Leinster. Signal not AVBL on ground Bellevue.

ADDITIONAL INFORMATION

Bird hazard exists (budgies, swallows, parrots and crows) in VCY of AD.

CHARTS RELATED TO THE AERODROME

1. WAC 3345.
 2. Also refer to AIP Departure and Approach Procedures.
-