

MOUNT HOTHAM**ELEV 4260****AVFAX CODE 3065**

VIC

UTC +10

YHOT

370254S

1472003E


VAR 12 DEG E

CERT

AD OPR MHSC Transportation Services Pty Ltd, PO Box 140, Bright, VIC, 3741. PH 03 5759 4444:

AD OPS 03 5159 6777 (H24): AD OPS Fax 03 5159 6776. ARO 0418 971 778: 0416 986 288.

Website: www.mthotham.com.au.

**REMARKS**

- AD Charges: All ACFT.
- PPR FM AD OPR for all night and non-RPT OPS, refer to website for OPR approval (PDF).
- Call-out fee applies for approved night OPS.

HANDLING SERVICES AND FACILITIES

JET A1 year round, 2200-0600 UTC DLY; JUN-SEP - 4HR PN. OT 24HR PN. CTC AD OPR.

Call-out fee applies weekends and PH during non-winter period. EFTPOS and credit cards only.

PASSENGER FACILITIES

June/September - PT/HC/BU/AC/LG/RF/WC. OT restricted hours.

APRONS AND TAXIWAYS

- TWY B not AVBL to ACFT ABV 5,700KG MTOW.
- TWY B AVBL to ACFT with a wingspan up to and not exceeding 15M.

AERODROME OBSTACLES

- Lit mast 4,460FT, BRG 291 DEG MAG 2,873M FM RWY 29 THR, 0.4M L of RCL.
- Trees:
 - BRG 297 DEG MAG 2,392M FM ARP. Infringes APCH SFC by 76FT.
 - BRG 285 DEG MAG 1,856M FM ARP. Infringes TNS by 13FT.
 - BRG 287 DEG MAG 1,644M FM ARP. Infringes TNS by 21FT.
 - BRG 286 DEG MAG 2,520M FM ARP. Infringes TNS by 50FT.
 - BRG 286 DEG MAG 1,654M FM ARP. Infringes TNS by 16FT.
 - BRG 288 DEG MAG 1,716M FM ARP. Infringes TNS by 34FT.

METEOROLOGICAL INFORMATION PROVIDED

- METAR/SPECI.
- AWIS Phone 03 8470 3217 - Report faults to BoM.
- AWIS FREQ 128.05 (one-second transmit pulse to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

11/29 111 48a PCN 24 /F /C /1138 (165PSI) /T

WID 30 RWS 90

AERODROME AND APPROACH LIGHTING

| | | | |
|-----------|---------|-------------|--|
| RWY 11/29 | LIRL(2) | | SDBY PWR AVBL BY PRIOR ARRANGEMENT |
| RWY 11/29 | RTIL(2) | | SDBY PWR AVBL BY PRIOR ARRANGEMENT |
| RWY 11 | PAPI(1) | 3.9 DEG42FT | SDBY PWR AVBL BY PRIOR ARRANGEMENT |
| RWY 29 | PAPI(1) | 3.0 DEG41FT | SDBY PWR AVBL BY PRIOR ARRANGEMENT |

- (1) Left side. PN REQ
- (2) PN REQ
 1. RWY edge light spacing: 11/29: 56M.
 2. From JUN to SEP the primary WDI located S RWY 11/29 will be yellow.
 3. Main PWR supply serviced by AD generator.

OTHER LIGHTING

1. Secondary PWR switchover time: 15 SEC.
2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 125.2 6500FT

LOCAL TRAFFIC REGULATIONS

All ACFT required to execute 180DEG turns at RWY end turning nodes only.

FLIGHT PROCEDURES

1. Right hand circuits required when OPR on RWY 29.
2. Pilots are requested to avoid overflying the Alpine National Park (Bogong Unit).

CTAF - AFRU 126.75

CHARTS RELATED TO THE AERODROME

1. WAC 3470.
 2. Also refer to AIP Departure and Approach Procedures.
-