CHRISTMAS ISLAND AVEAX CODE 9807

FLFV 913

2103

OTH UTC +7 YPXM 102702S 1054125E VAR 0 DEG E CERT

AD OPR Toll Remote Logistics - Locked Bag 860, Christmas Island, Indian Ocean, WA, 6798. Email: christmas.airport@tollgroup.com. PH Airport OPS +61 8 9164 8498. Mobile AH Duty Officer 0447 109 143. Fax 08 9164 8485.

REMARKS

- 1. AD Charges apply to all ACFT. Contact AD Manager for charges.
- PPR for all non RPT flights by fax or email to AD Manager at least 24HR prior to arrival.
- All ACFT arrivals at Christmas Island are treated as International arriving ACFT regardless of last port (including arrivals from Australian mainland) and are subject to Customs and Quarantine declaration.
- 4. Due limited space, operators should notify AD OPR of EST time of ARR.
- 5. This AD is a Security Controlled Airport.

HANDLING SERVICES AND FACILITIES

AIR BP: JET A1. HO by arrangement. Phone 0419 644 277 H24.

Altitude: FBO services. VIP services. H24. WC and watering services AVBL. Facilitation of

Customs/Quarantine/Airport permits. Email: operations@ciremovals.com.au. Phone 0407 474 968. VHF 129.25 Callsign 'Christmas Operations'.

PASSENGER FACILITIES

TX/HC/LG/WC (by prior arrangement).

AERODROME OBSTACLES

- OLS extensively infringed to west of RWY and extended centre line confine manoeuvring in IMC or night to east of RWY.
- Transitional SFC infringed both sides of RWY.
- 3. Terrain hazard beacon 994FT AMSL BRG 352 DEG MAG 1,979M FM ARP.
- Lit DVOR lightning rod 997FT AMSL BRG 358 DEG MAG 2,255M FM ARP.
- DVOR hazard LGT 994FT AMSL BRG 357 DEG MAG 2,246M FM ARP.
- 6. DME hazard LGT 992FT AMSL BRG 359 DEG MAG 2,261M FM ARP.
- Lit lighting towers 1,120FT AMSL BRG 333 DEG MAG 1,195M FM ARP.
- 8. Masts (lit for NGT OPS):
 - a. 1,185FT BRG 300 DEG MAG 2,110M FM ARP.
 - b. 1,045FT BRG 017 DEG MAG 1,893M FM ARP.

METEOROLOGICAL INFORMATION PROVIDED

- 1. TAF CAT A, METAR/SPECI.
- AWIS PH 08 6216 2606 Report faults to BoM.
- AWIS FREQ 126.25 Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

18/36 175 69a PCN 32 /F /A /1000 (145PSI) /T WID 45 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 18/36 LIRL(1) AFRU+PAL 132.2 SDBY PWR AVBL RWY 18/36 PTBL(3) BY PRIOR ARRANGEMENT

RWY 18 PAPI(2) AFRU+PAL 132.2 3.3 DEG53FT SDBY PWR AVBL RWY 36 PAPI(2) AFRU+PAL 132.2 3.0 DEG53FT SDBY PWR AVBL

- (1) Manual on REQ
- (2) Both sides Intensity automatic
- (3) EMERG only. 90MIN PN.
- RWY edge light spacing: 18/36: 60M.

OTHER LIGHTING

- 1. SDBY PWR switchover time: 15 SEC.
- 2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIS BRISBANE INO-1 INTL HF (1) 3476 5634 8879 13306 17961

WI SELCAL

FIS JAKARTA SEA 3 INTL HF (2) 3470 6556 11396 13318 17907

WI SELCAL

- (1) For flights departing to or arriving from Australian mainland and territories.
- (2) Flights departing to and arriving from the N.

RADIO NAVIGATION AND LANDING AIDS

DME XMX 112.4/71X 102548.5S 1054124.0E (1)
VOR XMX 112.4 102548.8S 1054121.6E

(1) Antenna ELEV 988FT.

All NAVAIDS Privately operated/Pilot Monitored.

LOCAL TRAFFIC REGULATIONS

- 1. All ACFT ABV 36,000KG MTOW to use RWY ends for 180DEG turns.
- APN not AVBL to other ACFT during C17 OPS.

FLIGHT PROCEDURES

- 1. Right hand circuits required on RWY 36.
- Straight-in approaches permitted at night. Recommended that ACFT arriving at night establish on final of instrument approach procedure.
- 3. Approach slope guidance (PAPI) REQ for all high capacity ACFT OPS.

CTAF - AFRU 132.2

ADDITIONAL INFORMATION

- Bird hazard exists.
- No RFFS provided.
- Expect moderate turbulence on late final approach when surface wind velocity above 15KT

 especially from easterly direction.
- Hazardous conditions may exist for ACFT when departing on RWY 18 with a E/SE crosswind ABV 10KT. Due to close proximity of small hill NE of RWS, ACFT are shielded until APRX 800M FM SOT RWY 18.

CHARTS RELATED TO THE AERODROME

- 1. WAC 3103.
- 2. Aerodrome Obstruction Chart Type A: June 2023.
- 3. Also refer to AIP Departure and Approach Procedures (DAP West).