

GNSS ARRIVAL PROCEDURES BUSSELTON, WA (YBLN)

23 MAY 2019

AWIS 128.05	FIA ML CEN 124.9	CTAF+AFRU 127.0	PAL 119.6		Bearings are Magnetic. Elevations in FEET AMSL
----------------	---------------------	--------------------	--------------	--	---------------------------------------------------

25 NM MSA

1900 BLN NDB 2400

B-220°
B-340°

REFERENCE WAYPOINT BLN NDB

BLN NDB 386

10 NM MSA 1900

AD ELEV 56

SECTOR A

MISSED APPROACH:

CLIMB ON TRACK TO 1000FT, THEN TURN AS APPROPRIATE TO TRACK 030° REFERENCE BLN NDB. CLIMB TO 2400FT.

NM TO BLN NDB	25	15	7	5	2	0												
CIRCLING MINIMA	A,B: 720-2.4			C: 880-4.0			D: 1140-5.0											
NM TO BLN NDB	3.9	3	2	1.5	1	0.7	0.2											
ALT (3° APCH PATH)	1900	1620	1300	1140	980	880	720											

SECTOR B

MISSED APPROACH:

CLIMB ON TRACK TO 1900FT.

NM TO BLN NDB	25	17	15	7	5	2	0											
CIRCLING MINIMA	A,B: 720-2.4			C: 880-4.0			D: 1140-5.0											
NM TO BLN NDB	5.5	5	4	3	2	1.5	1	0.7	0.2									
ALT (3° APCH PATH)	2400	2250	1940	1620	1300	1140	980	880	720									

Changes: PAL 119.6, Editorial.

BLNDG01-159