

1 DEC 2022

| | | | | | | | |
|-------------------------|--------------|--------------------|--------------|------------------------------|--|--------------------|--|
| ATIS 114.1 133.5 276 | ACD 128.1 | SMC 121.8 264.6 | TWR 118.3 | FIA (AH) BN CEN 120.55 | CTAF+AFRU (AH) AFRU+PAL (AH) 118.3 | AWIS (AH) 133.5 | Bearings are Magnetic Elevations in FEET AMSL |
|-------------------------|--------------|--------------------|--------------|------------------------------|--|--------------------|--|

DME USING TL DME REFERENCE WAYPOINT TL VOR

SPEED
MAX IAS 250KT
BELOW 10,000FT

10 NM MSA 3600

AD ELEV 18

SECTOR A

MISSED APPROACH:
TURN RIGHT,
TRACK 290°. CLIMB TO 4700FT OR AS DIRECTED BY ATC. MAX IAS 200KT.

| | | | | | | | | | | | | | | |
|------------------------|---------------|------|------|-------------|------|-------------|------|------|------|------|------|------|--|--|
| NM TO TL VOR | 25 | 15 | 13 | 7 | 5 | 0 | | | | | | | | |
| CIRCLING MINIMA | A,B: 1350-2.4 | | | C: 1350-4.0 | | D: 1350-5.0 | | | | | | | | |
| NM TO TL VOR | 13 | 12 | 11 | 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2.5 | | |
| ALT (3° APCH PATH) | 4700 | 4380 | 4060 | 3740 | 3420 | 3110 | 2790 | 2470 | 2150 | 1830 | 1510 | 1350 | | |

SECTOR B

MISSED APPROACH:
TURN LEFT OR RIGHT,
AS REQUIRED TRACK 290°. CLIMB TO 4700FT OR AS DIRECTED BY ATC.

| | | | | | | | | | | | | | | |
|------------------------|---------------|------|------|-------------|------|-------------|------|------|------|------|------|------|------|--|
| NM TO TL VOR | 25 | 15 | 14 | 10 | 5 | 0 | | | | | | | | |
| CIRCLING MINIMA | A,B: 1410-2.4 | | | C: 1410-4.0 | | D: 1410-5.0 | | | | | | | | |
| NM TO TL VOR | 12.8 | 12 | 11 | 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 0.9 | |
| ALT (3° APCH PATH) | 5200 | 4930 | 4610 | 4290 | 3970 | 3650 | 3330 | 3020 | 2700 | 2380 | 2060 | 1750 | 1410 | |

SECTOR C

MISSED APPROACH:
TURN LEFT,
TRACK 290°. CLIMB TO 4700FT OR AS DIRECTED BY ATC.

| | | | | | | | | | | | | | | |
|------------------------|---------------|------|------|-------------|------|-------------|------|------|------|--|--|--|--|--|
| NM TO TL VOR | 25 | 16 | 13 | 6 | 0 | | | | | | | | | |
| CIRCLING MINIMA | A,B: 2850-2.4 | | | C: 2850-4.0 | | D: 2850-5.0 | | | | | | | | |
| NM TO TL VOR | 10.4 | 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | | | | | |
| ALT (3° APCH PATH) | 5200 | 5080 | 4770 | 4450 | 4130 | 3810 | 3490 | 3180 | 2850 | | | | | |

Changes: SEC B DIST/ALT TABLE.

BTLDG01-173