AURUKUN AVFAX CODE 4508

FLFV 29



QLD UTC +10 YAUR
132114S 1414315E VAR 5 DEG E CERT
AD OPR Aurukun Shire Council, Aurukun, QLD, 4892. Email:
airport@aurukun.ald.gov.au. PH 07 4060 6811 (2200-0700 UTC), ARO

airport@aurukun.qid.gov.au. PH 07 4060 6811 (2200-0700 01 0428 743 874 (H24). Website: www.aurukun.qld.gov.au.

REMARKS

- This AD is a Security Controlled Airport.
- 24HR PPR for itinerant ACFT ABV 5,700KG MTOW and all pavement concessions
- 3. Alcohol is restricted within the Aurukun Shire and heavy penalties apply. Special provisions may apply to alcohol being transported on consignment and restrictions may vary from time to time. Further information is AVBL online: www.qld.gov.au/firstnations/health-staying-active/alcohol-smoking-drugs/community-alcohol-restrictions/remotediscrete-communities/aurukun, or phone 137 468.
- AD charges: all ACFT except RFDS and Defence Force. Current fees AVBL FM website.

HANDLING SERVICES AND FACILITIES

JET A1 AVBL for RPT ACFT or EMERG use. Underwing refuelling only. AVGAS not AVBL.

PASSENGER FACILITIES

LG/WC AVBL WI 1-2 HR of SKED OPS. Free WIFI and 4G MOB reception AVBL H24.

APRONS AND TAXIWAYS

- 1. TWY A Code C WID 18M bitumen seal.
- APN bitumen seal.

AERODROME OBSTACLES

- Unlit mast 223FT AMSL BRG 095 MAG 0.72NM FM ARP.
- 2. Trees:
 - a. 99FT AMSL 346 MAG 446M FM ARP infringes TNS by 7FT.
 - b. 93FT AMSL 318 MAG 500M FM ARP infringes TNS by 15FT.
 - c. 101FT AMSL 193 MAG 445M FM ARP infringes TNS by 8FT.

PHYSICAL CHARACTERISTICS

16/34 155 41a PCN 6 /F /B /850 (123PSI) /U Sealed WID 30 RWS 90

AERODROME AND APPROACH LIGHTING

RWY 16/34 LIRL AFRU+PAL 126.7 SDBY PWR AVBL RWY 16/34 PAPI(2) AFRU+PAL 126.7 3.0 DEG40FT SDBY PWR AVBL BY PRIOR ARRANGEMENT

- EMERG only.
- Left side.

RWY edge light spacing: 60M (white).

OTHER LIGHTING

- 1. SDBY PWR switchover time: 60 SEC.
- 2. TWY LGT: blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA BRISBANE CENTRE 122.1 Circuit area

CTAF - AFRU 126.7

LOCAL TRAFFIC REGULATIONS

- All ACFT must perform MAX RAD MNM speed turns at turn pads only to avoid RWY SFC damage.
- 2. Bays 1 and 2 marked DH8C and reserved for RPT ACFT during SKED OPS.

ADDITIONAL INFORMATION

Bird hazard exists RWY 16/34 and in VCY of AD (typically magpie-lark, cockatoo, galah, nankeen kestrel). Soaring kites sighted on occasion, APRX BRG 160 DEG MAG 800M FM SOT RWY 34 (ABV cemetery). ARO will conduct wildlife inspections immediately prior to arrival of SKED ACFT. Additional inspections AVBL on request, CTC ARO (call-out fee may apply).

CHARTS RELATED TO THE AERODROME

- 1. WAC 3112.
- 2. Also refer to AIP Departure and Approach Procedures.