ELEV 3106

COOMA - SNOWY MOUNTAINS 2113

AVFAX C	ODE	E 2113	
Number of Tank	81	NSW	
Rather ERSA-RDS	. 1	36180)2S
Ľ,	5	AD O	PR
	.	Jindal	byne
048° 9NM		H24 0	415
Cooma		REM	AR
2120		1.	A
	•		\$
			¢

1485826E

UTC +10

YCOM CERT

VAR 13 DEG E

AD OPR General Manager. Snowy Mountains Airport - Cooma. PO Box 35. Jindabyne, NSW, 2627, Email: aviation@snowymountainsairport.com.au, ARO 124 0415 582 069

REMARKS

- AD Charges (All exclude GST):
 - \$15.00/tonne MNM \$15.00 for single engined ACFT,
 - \$30 for other ACFT. Helicopters and Ultra-lights:
 - \$7.50/tonne MNM charge \$7.50. Night landing fee: \$30.00 from 2000 Local. Over night parking: \$15.00/night - \$45.00/week.

Commercial charters: 5 or more PAX - PAX tax \$12.50/PAX arriving and departing. Tonnage fee or PAX tax apply - which ever is higher. Charter flight require PN.

This AD is a Security Controlled Airport.

HANDLING SERVICES AND FACILITIES

Nil fuel AVBL.

PASSENGER FACILITIES

2.

TX - 02 6452 7777 (taxi's travel from Cooma township)/LG and RF - AVBL HS/WC - H24.

AERODROME OBSTACLES

Lit hazard lights:

- a. 3,775FT AMSL BRG 334 DEG MAG 5,056M FM ARP. Obstructs inner HZS by 559.06FT. Flashing.
- 3.558FT AMSL BRG 111 DEG MAG 2.284M FM ARP. Obstructs inner HZS by b. 342.52FT. Flashing.
- 3.270FT AMSL BRG 352 DEG MAG 3.616M FM ARP. Obstructs RWY 36 TKOF climb C. SFC by 63.65FT.
- d. 3,223FT AMSL BRG 358 DEG MAG 3,698M FM ARP. Obstructs RWY 36 TKOF climb SFC by 8.53FT.
- e. 3.248FT AMSL BRG 002 DEG MAG 3.944M FM ARP. Obstructs RWY 36 TKOF climb SFC by 17.72FT.

METEOROLOGICAL INFORMATION PROVIDED

- TAF CAT D. METAR/SPECI. 1.
- AWIS PH 02 9353 6414 Report faults to BoM. 2.

PHYSICAL CHARACTERISTICS

18/36 180 70a PCN 12 /F /A /650 (94PSI) /T WID 30 **BWS 150**

AERODROME AND APPROACH LIGHTING

RWY 18/36 I IRI AFRU+PAL 118.1 SDBY PWR AVBL RWY 18/36 PAPI(1) AFRU+PAL 118.1 3.0 DEG40FT SDBY PWR AVBL (1)Left side. Lighting status confirmed on PAL.

RWY edge light spacing: 18/36: 60M.

OTHER LIGHTING

HBN

HBNs: Located NNW and SE of AD.

SDBY PWR supplies by AD generator in the event of mains PWR failure. 1.

2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

- FIA MEI BOURNE CENTRE
- 120.75 Circuit area (On ground COM contact 119.4)

RADIO NAVIGATION AND LANDING AIDS

- DME
 COM
 114.0/ 87X
 362115.5S
 1485727.7E
 (1)

 NDB
 COM
 293
 362113.6S
 1485727.1E
 Range 80 (HN 70)
 (2)

 (1)
 Antenna ELEV 3026FT Pilot monitored.
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (2)
 (2)
 (2)
 (1)
 (2)
 (2)
 (3)
 (3)
 (3)
 (3)
 (2)
 (3)
 (3)
 (3)
 (2)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
 (3)
- Anterina ELEV 3026FT Pilot monitored
 003/3.3 to ARP Pilot monitored.

1. Parking restrictions

- a. To avoid OBST to RPT ACFT, parking for GA ACFT BLW 5,700KG MTOW AVBL E and ADJ to RPT Bay 3 and 3A.
- b. ACFT parking in RPT bays require PN on Monday, Thursday, Friday 0800-1800 Local.
- c. RPT Bays 1 and 2 suitable up to DH8D.
- d. RPT Bays 1A and 2A suitable up to SF34.
- e. RPT Bays 3 and 3A suitable up to JS32.

2. RWY 18/36 turning restrictions

- a. Pilots to use full RWY width when turning (no sharp turns).
- b. ACFT ABV 5,700KG MTOW must only turn at the turn pads.

CTAF - AFRU 118.1

ADDITIONAL INFORMATION

- 1. Bird and animal hazard exists.
- Gliders OPR FM Bunyan Airstrip 12.5NM NE Cooma HJ, generally JF, and monitor 122.7, or CTAF when WI 10NM of Cooma AD. Tug ACFT when airborne monitor CTAF and 122.7.
- Polo Flat airfield located adjacent to Cooma Township and 9NM NE of Cooma Snowy Mountains AD. Polo Flat has a separate ERSA entry.
- 4. Risk of snowfall or heavy frost year-round. Highest risk from May to October. No snow clearing or de-icing equipment AVBL.

CHARTS RELATED TO THE AERODROME

- 1. WAC 3470.
- 2. Also refer to AIP Departure and Approach Procedures.