DUKETON GOLD				ELEV 1770
AVFAX CODE 6115				
BI System Sy	dgparo@regisresour 0456 649 886: 08 64 REMARKS Restricted OPS PPF HANDLING SERV	rces.com. AD Manag 124 9339. AD Manag R. /ICES AND FACII	LITIES	
AERODROME OBSTACLES Lit masts: a. 2.011FT AMSL BRG 138 DEG MAG 2.3NM FM ARP. Infringes inner HZS by 105FT.				
			NM FM ARP. Infringes	
PHYSICAL CHARACTERISTICS				
18/36		N 27 /F /B /1200 (17	74PSI) /T Grooved	WID 30 RWS 150
AERODROME AND APPROACH LIGHTING				
RWY 18/36	6 PAPI(2)		3.0 DEG48.5FT	BY PRIOR
RWY 18/36	6 PTBL(1)			ARRANGEMENT BY PRIOR ARRANGEMENT
 EMERG only requires 60MIN PN to Mill Control PH: 08 6424 9339. Left side only. Manual activation of PAPI AVBL with 60MIN PN. RWY edge light spacing: 18/36 58.8M (PTBL). No mains PWR AVBL - PRI source of PWR is derived FM a generator. 				
ATS AND AERODROME COMMUNICATION FACILITIES				
FIA UNICOM	MELBOURNE CEN	TRE	118.95 126.7 (1)	
LOCAL TRAFFIC REGULATIONS				
 RWY 18/36: All fixed wing ACFT ABV 5,700KG must roll through to RWY end and make MAX RAD turns at MNM speed at all turning nodes to avoid SFC damage. 				

- 2. Itinerant PRKG CTC AD Manager/ARO.
- 3. All ACFT to follow APN markings.
- All jet ACFT to use idle PWR for movements on the APN with the exception of breakaway thrust to initiate TAX. ACFT that cannot comply with this restriction must advise the AD OPR prior to DEP.

FLIGHT PROCEDURES

Right hand CCTS RWY 18.

CTAF 126.7

AFRU not AVBL.

ADDITIONAL INFORMATION

- 1. Blasting conducted at mine East of AD, contact ARO for times.
- Increased bird activity (Plover and Bustard) on RWY 18/36 and RWS. Mostly active after rain.

CHARTS RELATED TO THE AERODROME

- 1. WAC 3345.
- 2. Also refer AIP Departure and Approach Procedures.