


**KARARA****ELEV 1019****AVFAX CODE 6013**

WA  
 291258S 1164112E UTC +8 YKAR  
 AD OPR Karara Mining Ltd, Level 2, 216 St Georges Tce, Perth, WA, 6000. CERT  
 Email: aro@kararamining.com.au. PH 08 6298 1888. ARO 0438 926 212.

**REMARKS**

Restricted OPS. PPR from AD OPR.

**AERODROME OBSTACLES**

1. Numerous OBST penetrate inner HZS and conical SFC.
  - a. Terrain - LCA BTN 085 DEG MAG and 095 DEG MAG 4,037M to 4,907M FM ARP 1,198FT.
  - b. Terrain - LCA BTN 098 DEG MAG and 115 DEG MAG 4,846M to 5,420M FM ARP 1,198FT.
  - c. Power poles BTN 319 DEG MAG and 008 DEG MAG 1.6NM FM ARP, up to 100FT.
2. Lit mast - LCA 024 DEG MAG 4,223M FM ARP 1,312 FT AMSL.
3. Perimeter fence unmarked and unlit, north side of entire length of RWY 12/30 and south of SOT RWY 30, 82M FM RWY 12/30 CL. Infringes transitional SFC by 4FT.

**PHYSICAL CHARACTERISTICS**

12/30 117 46a PCN 39 / F / A / 1415 (205PSI) / T Sealed WID 30 RWS 150

**AERODROME AND APPROACH LIGHTING**

RWY 12/30 PAPI(2) AFRU+PAL 126.9 3.0 DEG41.5FT

RWY 12/30 PTBL(1)

BY PRIOR  
ARRANGEMENT

- (1) EMERG only. 2HR PN.
- (2) Left side only.
  1. PAPI power supplied by generators.
  2. Allow 15 seconds for generators to start up and positive confirmation of AD LGT activation communicated through CTAF.
  3. PAPI intensity HN manually controlled by ARO via CTAF 126.9.

**ATS AND AERODROME COMMUNICATION FACILITIES**

FIA MELBOURNE CENTRE 124.8 Circuit area

UNICOM KARARA UNICOM 126.9 (1)

- (1) CS "Karara UNICOM" when ARO in attendance.

**LOCAL TRAFFIC REGULATIONS**

All ACFT ABV 5,700KG MTOW to make MAX RAD, MNM speed turns at turning nodes only.

**CTAF - AFRU** 126.9**ADDITIONAL INFORMATION**

Caution: intermittent blasting and associated potential fly-rock at Karara mine site located approximately 5-8NM ENE of ARP.

**CHARTS RELATED TO THE AERODROME**

1. WAC 3351.
2. Also refer AIP Departure and Approach Procedures.