
# LISMORE AVFAX CODE 2087

FLFV 35



NSW UTC +10 YLIS 284936S 1531527E VAR 11 DEG E CERT AD OPR Lismore City Council, PO Box 23A, Lismore, NSW, 2480. Email: council@lismore.nsw.gov.au. PH H24 02 6625 0500 or 0409 078 338.

Website: www.lismore.nsw.gov.au.

# **REMARKS**

- 1. AD Charges. Landing, Touch and Go, Stop and Go and parking fees apply to all non RPT ACFT. Refer to website.
- 2. This AD is a Security Controlled Airport.
- 3. Terminal closed outside of RPT movements.

#### HANDLING SERVICES AND FACILITIES

BP - Air BP Lismore (John Habib): 2200-0700 UTC DLY, BH 1HR PN, AH PN. Phone 02 6621 6940 or 0412 666 902. AH call-out fee applies. AVGAS, H24 Cardswipe AVGAS bowser - Air BP card only. World Fuel Services and Lismore JET A1 airport and off-airport JET A1 refuelling and deliveries in the Northern Rivers Region AVBL with 1HR PN. H24 World Fuel Services AVGAS bowser WFS carnet card and CC

### PASSENGER FACILITIES

PT/TX (131 008)/HC/AC/LG/RF/WC (H24)/ME.

Note: PT/TX/HC/AC/LG and RF AVBL at terminal at Southern end, WC and ME at N end.

(via smart-phone app) PH 0422 441 277.

#### **APRONS AND TAXIWAYS**

- Unsealed pavement not AVBL to ACFT ABV 3,500KG MTOW.
- 2. Northern TWY and APN not AVBL to ACFT above 5,700KG.
- 3. RPT APN Parking Restriction: If Bay 2A is occupied, Bays 1 and 2 N/A. If Bays 1 or 2 occupied, Bay 2A N/A.

# **AERODROME OBSTACLES**

Power pole 60FT AGL PSN 285018S 1531542E APRX BRG 215 MAG 1,048M FM ARP. Infringes TNS by 9.5FT.

# METEOROLOGICAL INFORMATION PROVIDED

- 1. TAF CAT C, METAR/SPECI.
- 2. AWIS Phone 02 9353 6431 Report faults to BoM.
- AWIS FREQ 128.05 Report faults to AD OPR.

#### PHYSICAL CHARACTERISTICS

15/33 146 54a PCN 15 /F /C /1200 (174PSI) /T WID 30 RWS 150

1. Horizontal SFC significantly infringed; caution night circling.

Side transitions infringed.

#### AERODROME AND APPROACH LIGHTING

RWY 15/33 LIRL AFRU+PAL 132.45 SDBY PWR AVBL RWY 15/33 PAPI(1) AFRU+PAL 132.45 3.0 DEG42FT SDBY PWR AVBL RWY 15/33 RTIL AFRU+PAL 132.45 SDBY PWR AVBL

Left side.

- 1. RWY edge light spacing: 15/33: 58M.
- 2. PAL only operates PAPI and RTIL HJ.

#### OTHER LIGHTING

- 1. TWY LGT: Blue edge.
- 2. 1 MIOL, 15 LIOL
- Secondary PWR switchover time: 15 SEC.

#### ATS AND AERODROME COMMUNICATION FACILITIES

FIA BRISBANE CENTRE 120.3 On Ground

#### LOCAL TRAFFIC REGULATIONS

- Non RPT ACFT require prior permission to use the RPT Apron.
- 2. All ACFT movements restricted to designated RWY, TWY and APN only.

#### FLIGHT PROCEDURES

During Ballina (YBNA) SFIS hours of operation only, all IFR aircraft commencing a published YLIS RWY 33 instrument approach transiting the YBNA MBA via an initial waypoint from outside the MBA, will not be required to broadcast on the YBNA MBA frequency. Those IFR aircraft will broadcast on the YLIS CTAF and receive traffic information from ATS on the area frequency.

# **CTAF - AFRU 132.45**

# NOISE ABATEMENT PROCEDURES

- A farm located approximately 900M FM the DEP end of RWY 15 and slightly left of the extended centreline is a noise-sensitive area. Pilots should avoid turning over this location and, if possible, maintain RWY HDG until clear.
- 2. Fly neighbourly guidance in effect, document AVBL FM website.

# ADDITIONAL INFORMATION

- 1. Bird, flying fox (bat) and kangaroo hazard at AD.
- Model ACFT OPR WI 500M RAD of PSN 285030.00S 1531742.00E BRG 103 MAG 2.2NM FM ARP SFC to 1.000FT AGL.

### CHARTS RELATED TO THE AERODROME

- 1. WAC 3357.
- 2. Also refer to AIP Departure and Approach Procedures.