


MOUNT MAGNET**ELEV 1354****AVFAX CODE 6011**

WA
280658S 1175030E UTC +8 YMOG
VAR 0 DEG E CERT
AD OPR Shire of Mount Magnet, PO Box 62, Mt Magnet, WA, 6638. Email:
works@mtmagnet.wa.gov.au. PH 08 9963 3000 BH. ARO AH 0427 634 241 or
0409 058 809. Fax 08 9963 4133.

REMARKS

1. AD charges apply. Contact AD Operator.
2. This AD is a Security Controlled Airport.

AERODROME OBSTACLES

1. Fence 989M FM SOT RWY 04, 5FT AGL.
2. Primary IWI 1,362FT AMSL BRG 017 DEG MAG 100M FM ARP.
Infringes transitional SFC by 2FT.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT D, METAR/SPECI.
2. AWIS PH 08 6216 2627 - report faults to BoM.
3. AWIS FREQ 122.975 (requires one-second pulse to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

| | | | | | |
|-------|-----|-----|--|--------|--------|
| 04/22 | 035 | 30c | 5700/735 (107PSI) Unrated. Red silt sand | WID 30 | RWS 90 |
| 16/34 | 157 | 59a | PCN 9 /F /A /850 (123PSI) /U | WID 30 | RWS 90 |

AERODROME AND APPROACH LIGHTING

RWY 16/34 LIRL AFRU+PAL 126.7 SDBY PWR AVBL

1. RWY edge light spacing: 16/34: 60M.
2. Secondary power supply requires 10 SEC switchover time for automatic generator to fully activate.

OTHER LIGHTING

TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 124.8 Circuit Area

RADIO NAVIGATION AND LANDING AIDS

NDB MOG 395 280350.8S 1175037.4E Range 85 (HN 85) (1)
(1) Pilot monitored - 183/3.4 to ARP.

LOCAL TRAFFIC REGULATIONS

1. ACFT ABV 5,700KG are required to use RWY 16/34 only and to taxi on RCL and turn at turning nodes. All turns to be MNM speed, MAX RAD.
2. Due to limited apron space H24 PN required for all non RPT ACFT above 5,700KG.
3. Light ACFT PRKG Bay at S side of APN. Tie-down (not rated) provided.

CTAF - AFRU 126.7

ADDITIONAL INFORMATION

Inspections are carried out on MON, WED, THU and FRI. Additional inspections are AVBL and with 60 MIN PN.

CHARTS RELATED TO THE AERODROME

1. WAC 3351.
2. Also refer to AIP Departure and Approach Procedures.