WOODIE WOODIE

ELEV 889

I

AVFAX CODE 6823								
* * 10 W	D0° 2.3NM loodie Woodie amp	2. Day OPS 3. No mobi	visupervisors 460 7037. A ed OPS: PPI S only. ile coverage ERVICES /	Pty Ltd, ©consn RO AH E R from A on site.	ninerals.com.au Emergency 08 s D OPR. CILITIES	West Perth J. PH On si	te 08 9460	
	Ground handling agents. Contact ARO.							
Fuel facilities: Limited JET A1. Private installation. Contact ARO. PASSENGER FACILITIES LG/WC.								
AERODROME OBSTACLES Lit mast 1,042FT AMSL BRG 103 DEG MAG 3,329M FM ARP. Infringes inner HZS by 7FT. PHYSICAL CHARACTERISTICS								
14/32		6a PCN 31/F	/A /1000 (14	5PSI) /T		WID 30	RWS 150	
AERODROME AND APPROACH LIGHTING								
RWY 14/32 RWY 14/32	PAPI(1)		3.0 DE	G48FT	BY PRIO		
 Left hand side. 30MIN PN to ARO. EMERG only 90MIN PN to ARO. RWY edge light spacing: RWY 14/32: 90M apart (PTBL). RWY 14 PAPI units located 430M from RWY 14 THR due 1.47% downward slope - reduced landing distance may be applicable. No mains power AVBL - power supply via on site generator. 								
OTHER LI								
TWY LGT: Nil. ATS AND AERODROME COMMUNICATION FACILITIES								
FIA UNICOM	-	NE CENTRE		-	TIES ot AVBL on Gro	ound		

LOCAL TRAFFIC REGULATIONS

- All ACFT ABV 5,700KG MTOW must use turning nodes for 180DEG turns at MAX radius, MNM speed.
- 2. ACFT must follow lead-in lines.
- 3. RWY 32: all ACFT ABV 5,700KG MTOW must run-out to turning node when landing.
- 4. RWS not maintained for ACFT OPS.

CTAF 126.7

ADDITIONAL INFORMATION

Blasting scheduled daily however occurs intermittently. Approval must be obtained from ARO or airport manager prior to blasting.

CHARTS RELATED TO THE AERODROME

- 1. WAC 3230.
- 2. Also refer to AIP Departure and Approach Procedures.