

GOLD COAST

RWY	(CN)	TORA	TODA	ASDA	LDA
14	(4)	2342 (7684)	2402 (7880) (3.65%)	2342 (7684)	2342 (7684)

RESA dimensions 90M X 90M commences from RWS end.

1. Note: Fence 2FT ABV and 2M S of RWS end is not taken into account in the calculation of TODA GRAD and STODA.

2. RWY 14 RWS 300 - OPR restriction: TKOF RWS 150.

32	(4)	2492 (8176)	2552 (8373) (3.43%)	2492 (8176)	2042 (6699)
----	-----	-------------	---------------------	-------------	-------------

RESA dimensions 90M X 90M commences from RWS end.

RWY 32 DTHR permanently 300M.

Slope 0.1% down to SE. RWY WID 45 RWS WID 300

17	(1)	582 (1909)	642 (2106) (4.8%)	582 (1909)	582 (1909)
----	-----	------------	-------------------	------------	------------

35	(1)	582 (1909)	612 (2008) (4.2%)	582 (1909)	582 (1909)
----	-----	------------	-------------------	------------	------------

Slope 0.2% down to S. RWY WID 18 RWS WID 90

SUPPLEMENTARY TAKEOFF DISTANCES

RWY14- 1710(5610)(1.6) 1945(6381)(1.9) 2072(6798)(2.2) 2171(7123)(2.5) 2349(7707)(3.3)

RWY32- 1451(4760)(2.2) 1972(6470)(2.5) 2531(8304)(3.3)

TAXIWAY INTERSECTION DECLARED DISTANCES

RWY14-	TKOF from TWY B;	RWY remaining 1435(4708)	reduce all DIST by 907(2976)
RWY14-	TKOF from TWY H;	RWY remaining 1737(5699)	reduce all DIST by 605(1985)
RWY32-	TKOF from TWY D;	RWY remaining 1685(5528)	reduce all DIST by 807(2648)
RWY32-	TKOF from TWY F;	RWY remaining 1575(5167)	reduce all DIST by 917(3008)
RWY32-	TKOF from TWY K;	RWY remaining 2342(7684)	reduce all DIST by 150(492)